

AUTOCLEAR® Mailscreen® 3005

Fast, Easy, Hands-free, Compact
Metal, Mailbomb and Pipebomb Screener



AUTOCLEAR is the leading worldwide producer of fast, reliable and sophisticated X-ray, Metal and Trace Detection screening systems. Visit us at www.autoclearus.com. Our advanced systems and options can be integrated or leased.

Mailbombs are a hazardous safety concern for target individuals and organizations, often concealed in a seemingly routine thin package or letter. The Mailscreen® 3005 can screen parcels and packets of mail that should NOT be opened without expert inspection.

The Mailscreen® 3005 enables detection of metallic letterbomb components such as detonators, timing devices, shielding and batteries. Objects are screened from both sides as they pass through the scanner zone: (15.6" x 2.75" opening, 39.6 cm x 7 cm with unlimited length).

The detector will automatically alarm, including visually, when it senses a factory preset level of metal. A factory provided test card is available to verify performance. The Mailscreen™ is very affordable, portable, and can process considerable mail.

Features and Benefits

- Small, lightweight, versatile and safe.
- Detects metal objects, ferrous or non-ferrous, using independent circuit coils, from a large item to a small razor blade, detonator or watch battery used in bombs.
- Easy, automated operation with no setup required.
- A.C. and battery backup standard.
- Harmless to film, tapes, CD's, DVD's which rarely contain metal.
- 100% digital reliability with immunity to external interference.
- Ignores staples, pins, tags and virtually all paper clips, common in mail.
- Detects UK Forensic Standard metal disc.
- 12 month warranty parts & labor.
- Available Sensitivity Adjustment Switch for supervisor control.

PHYSICAL DIMENSIONS:

Height:	13" (33 cm)	Width:	18" (45.7 cm)
Depth:	18" (45.7 cm)	Weight:	37 lbs (16.8 kg)

TEMPERATURE RANGE: 10° C - 50° C

CONTROL PANEL: Power on/off, audible volume on/off (sound alert), audible and visual alarms & light indicators. Complies with applicable international standards on electrical safety, EMC and CE.

ELECTRICAL: 110 or 220 Volts. Includes 9-volt alkaline battery back-up power. Optional rechargeable 9-V NiCad

www.autoclearus.com

Technology Labs & Headquarters Plant

2 Gardner Road
Fairfield, NJ 07004-2206 USA
Tel: 1 (973) 276-6161
Fax: 1 (973) 276-6162
info@autoclearus.com

Central EU

eu@autoclearus.com
Tel: + 33 2 38 61 97 00
Fax: + 33 2 38 61 97 01

Southern EU

seu@autoclearus.com

Northern EU

neu@autoclearus.com

Canada & Scintrex

info@scintrextrace.com
300 Parkdale Ave., Ottawa
Ontario, Canada K1Y 1G2
Tel: 1 (613) 224-1061
Fax: 1 (613) 224-2603

Asia Southeast & North

sasia@autoclearus.com
nasia@autoclearus.com
china@autoclearus.com

Latin America

latina@autoclearus.com

Middle East

ME@autoclearus.com
Dubai, UAE
Tel: + 971 6 557 4505
Fax: + 971 6 557 4507

Western U.S.

sw@autoclearus.com

ISO 9001-2000 registered
Modifications reserved 2009-2011
© autoclear llc

Mailrooms • Lobbies • Events • Rentals
Professional Offices • Police • Executive Mail

AUTOCLEAR®

autoclearus.com

Scintrex® • CheckGate® • Dynavision® • Control Screening® • Federal Labs®
U.S. Canada Europe Dubai Latin America Beijing Hong Kong Singapore

Leading contraband threat detection & field support, since 1937